Environmental Product Declaration



EPD[®]

In accordance with ISO 14025 and EN 15804:2012+A2:2019 for:

Precast concrete products - Solid walls

from

Perdanga, UAB



Programme: Programme operator: EPD registration number: Publication date: Valid until: The International EPD® System, <u>www.environdec.com</u> EPD International AB S-P-04750 2021-10-06 2026-10-05

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com







Environmental Product Declaration

This is an Environmental Product Declaration for precast concrete wall – solid wall, produced by Perdanga, UAB. The declaration is registered in accordance with the EPD programme of the International EPD® System and the Product Category Rules for Construction Products 2019:14, version 1.1. The EPD are used in both business-to-business (B2B) and business-to-consumer (B2C) communication.

Company information

Owner of the EPD: Perdanga, UAB e-mail: <u>valaitis@perdanga.lt</u> www.perdanga.lt

<u>Description of the organisation</u>: The factory counts its age since 1961. Since 1992 the enterprise has been registered as the Limited Liability Company "Perdanga". Perdanga is the one of the largest producers of concrete products in Lithuania with a turnover of 28 MEUR. In year 2003 company established second factory in Vilnius. The Company's products were used in major construction projects: Klaipeda city waste-water treatment plant, Butinge Oil Terminal, Mazeikiai Refinery, Klaipeda Container Terminal, Cruise Terminal, production facilities of foreign capital companies "Philip Morris", Master Foods. Perdanga production is also exported to neighbouring countries – Latvia, Russia, Sweden, and Norway. Company has implemented Quality management systems EN ISO 9001:2015 and EN ISO 14001:2015

<u>Product-related or management system-related certifications:</u> Solid walls have CE marking and are produced according to requirements of EN 14992. Common aspects which apply to all precast products are specified in EN 13369 and EN 206-1.

Name and location of production site(s): Perdanga, UAB Dubysos str. 27, 91181 Klaipeda, Lithuania

Product information

Product name: Solid wall

<u>Product description</u>: Precast concrete wall elements – solid walls - are an integral part of buildings made of prefabricated reinforced concrete. Solid walls are used as internal load-bearing structures or self-supporting partition structures in various types of buildings. Depending on the geometric dimensions of the element partition structures are produced with a thickness of 60-100 mm. Internal retaining walls usually perform several functions:

- supports flooring structures and loads on it,
- plays the role of a vertical stabilizing element (diaphragm),
- serves as an acoustic barrier isolating both impact and airborne sound,
- works as a firewall between different fire compartments.

Thickness of the precast concrete wall, types of connections with other elements, concrete class, intensity of reinforcement and thickness of concrete cover are selected taking into account functions listed above. Retaining walls usually have thickness of 100-240 mm.

Solid walls serve perfectly as a vertical stabilizing element (stiffness diaphragm or, when combined into a spatial structure, stiffness core) in multi-purpose buildings.



Usually diaphragms are installed in the transverse and longitudinal directions between columns in frame buildings. Diaphragms take over the vertical and horizontal loads acting on the building and ensure it's rigidity and stability.

Rigidity cores are used in tower-type buildings as a stabilizing element. Stiffness cores are obtained by rigid joints connecting prefabricated solid wall elements into a closed spatial structure. Stair blocks and elevator shafts serve this purpose.

Class of concrete used for the production of walls is specified in the design documentation. Unless otherwise stated, concrete class C30/37 is used. Flexible rope loops are used for wall connection in vertical joint. Solid walls are usually reinforced with two reinforcement meshes. Mesh specification is described in product reinforcement drawing.

Solid walls can have round or rectangular holes for installing of communications and channels for electrical installation. Steel inserts may be provided for connection of other structures.

Solid wals can also be used as external partitions of a building. In this case, single-layer walls are manufactured in the factory and delivered and installed on the construction site. The thermal insulation material is glued and mechanically attached to the reinforced concrete walls after assembly of the building. Plastering, linear or segment finishing is used to complete the façade. In such way, a seamless facade is obtained.

UN CPC code: 375

Geographical scope: Europe

LCA information

<u>Functional unit / declared unit:</u> In accordance with the PCR the declared unit is 1 metric tonne of the product.

<u>Reference service life:</u> The reference service life for the solid wall is set at 100 years.

<u>Time representativeness</u>: Primary data was collected internally. The production data refers to the average of the year 2020.

<u>Database(s) and LCA software used:</u> The Ecoinvent database provides the life cycle inventory data for the raw and process materials obtained from the background system. The used database is Ecoinvent 3.6. The LCA software used is One Click LCA.

Description of system boundaries:

Cradle to gate with options, modules C1-C4 and module D. The LCA was carried out considering the Product stage phases (A1, A2, A3), Distribution (A4), End of life (C1, C2, C3, C4), Potential environmental benefits (D) in accordance with EN 15804.

<u>Data quality:</u> The foreground data collected internally is based on yearly production amounts and extrapolations of measurements on specific machines and plants. Overall, the data quality can be described as good. The primary data collection has been done thoroughly.

<u>Cut-off criteria</u>: Life cycle inventory data for a minimum of 99% of total material and energy input flows have been included in the life cycle analysis. Although only materials having in summa less than 1% of weight of product were not used in calculations.





System diagram:



Product stage:

A1: This stage considers the extraction and processing of raw materials as well as energy consumption. A2: The raw materials are transported to the manufacturing plant. In this case, the model includes road transportation of each raw material.

A3: This stage includes the manufacture of products and packaging. It also considers the energy consumption and waste generated at production plant.

Modules declared:

	Pr s	oduo stage	ct	Const pro sta	ruction cess age	Use stage End of life stage						Resource recovery stage					
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
Module	A 1	A2	A3	A 4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	х	х	х	х	MND	MND	MND	MND	MND	MND	MND	MND	х	х	Х	х	Х

Description of the system boundary (X = Included in LCA; MND = Module Not declared; MNR = Module Not relevant)

Production process description

Solid walls are produced on tilting tables. Before every casting tables should be cleaned from small concrete particles, rust and excess oil. Water based oil is used for surface oiling. Desirable geometrical shape and height of element is exceeded by using aluminium frame moulds with plywood surface. Windows, doors openings are planned by setting additional moulds for them as well as for openings for



HVAC, plumbing and sewerage systems. Pipes for electrical wires and boxes for electrical sockets also can be casted in. Wire loops and steel inserts for connection between structural elements or other special purposes are placed in designed possition. After pouring of concrete initial leveling is done manually. Shock vibration is used for concrete compaction. Free surface is mechanically troweled to get desirable surface quality. Walls are delivered to production stockyard or directly to construction site.

Construction process stage:

A4: This stage includes transport from the production gate to the construction site where the product shall be installed. Transportation is calculated based on data form manufacturer and a scenario with the parameters described in the following table. The transportation doesn't cause losses as products are packaged properly.

Parameter	Value/Description
Vehicle type used for transport	EURO 5 truck with a trailer with an average load of 16-32t
Distance	70 % of production: Truck – 158 km. 30 % of production: Truck – 278 km, Ship – 276 km.
Capacity utilization	56 % of the capacity in volume (truck), 50 % of the capacity in volume (ship)

Use stage:

In normal use scenario, it is assumed that no maintenance (B2), repair (B3), replacement (B4) and refurbishment (B5) is needed.

End of Life stage:

This stage includes the following modules:

C1: Deconstruction, dismantling, demolition

Consumption of fuel in demolition process is calculated according to transported mass. Energy consumption demolition is 10 kWh for 1000 kg. The source of energy is diesel fuel used by work machines.

C2: Transport of the discarded product to the processing site

It is estimated that there is no mass loss during the use of the product, therefore the end-of-life product is assumed that it has the same weight with the declared product. All the end-of-life product is assumed to be sent to the closest facilities such as recycling and landfill. Transportation distance to the closest disposal area is estimated as 50 km and the transportation method is lorry which is the most common.

C3: Waste processing for reuse, recovery and/or recycling

Based on Europe average 90% of steel are transformed into secondary material in a recycling plant. According to European Commission Waste Framework Directive by 2020, the preparing for re-use, recycling and other material recovery of non-hazardous construction and demolition waste shall be increased to a minimum of 70 % by weight. It is assumed that 70% of the concrete waste is recycled.

C4: Discharge (disposal)

The remaining 30 % of concrete and 10 % of steel are assumed to be sent to the landfill.

EPD[®]





Benefits and loads beyond the system boundary (D):

Benefits of recyclable waste generated in the phase C3 are considered in the phase D. The recycled steel has been modelled to avoid use of primary materials. The scrap content in the studied product has been acknowledged and only the mass of primary steel in the product provides the benefit to avoid double counting. 70 % of concrete is assumed to be converted into a raw material.

Content information

Product components	Weight, kg	Weight, %
Cement	164.88	16.49
Gravel	74.59	7.46
Breakstone	317.99	31.80
Sand	317.99	31.80
Reinforcement	58.29	5.83
Water	65.95	6.60
Additives	0.31	0.03
TOTAL	1000	100

No dangerous substances from the candidate list of SVHC for Authorisation are used in the product

Packaging

Distribution packaging: wooden gaskets.

After use, packaging materials can be re-used or recycled.



Environmental Information

CORE ENVIRONMENTAL IMPACT INDICATORS - EN 15804+A2, PEF

Results per functional or declared unit											
Impact category	Unit	A1	A2	A3	A1-A3	A 4	C1	C2	C3	C4	D
GWP – total	kg CO2e	2.16E2	4.38E0	4.39E0	2.24E2	1.83E1	3.30E0	4.55E0	4.71E0	1.52E0	-2.88E1
GWP – fossil	kg CO2e	2.13E2	4.37E0	4.31E0	2.22E2	1.84E1	3.30E0	4.54E0	4.77E0	1.52E0	-2.88E1
GWP – biogenic	kg CO2e	2.38E0	8.59E-3	6.34E-2	2.45E0	1.26E-2	9.17E-4	3.30E-3	-6.78E-2	3.01E-3	8.95E-3
GWP – LULUC	kg CO2e	7.80E-2	2.30E-3	1.13E-2	9.16E-2	5.84E-3	2.79E-4	1.37E-3	2.51E-3	4.51E-4	-1.16E-2
Ozone depletion pot.	kg CFC11e	1.04E-5	9.21E-7	4.60E-7	1.18E-5	4.30E-6	7.12E-7	1.07E-6	1.62E-6	6.25E-7	-1.25E-6
Acidification potential	mol H+e	7.43E-1	2.31E-2	2.54E-2	7.91E-1	9.94E-2	3.45E-2	1.91E-2	4.88E-2	1.44E-2	-1.5E-1
EP-freshwater ²⁾	kg Pe	6.47E-3	7.34E-5	3.21E-4	6.86E-3	1.47E-4	1.33E-5	3.70E-5	1.32E-4	1.83E-5	-1.75E-3
EP-marine	kg Ne	1.69E-1	7.40E-3	5.68E-3	1.82E-1	2.85E-2	1.52E-2	5.75E-3	1.48E-2	4.96E-3	-2.98E-2
EP-terrestrial	mol Ne	1.97E0	8.19E-2	6.83E-2	2.12E0	3.16E-1	1.67E-1	6.35E-2	1.65E-1	5.47E-2	-3.52E-1
POCP ("smog")	kg NMVOCe	6.37E-1	2.45E-2	2.08E-2	6.82E-1	9.72E-2	4.59E-2	2.04E-2	4.73E-2	1.59E-2	-1.46E-1
ADP-minerals & metals	kg Sbe	2.19E-3	6.48E-5	5.56E-5	2.31E-3	3.07E-4	5.03E-6	7.75E-5	1.04E-4	1.39E-5	-1.02E-3
ADP-fossil resources	MJ	1.55E3	6.70E1	6.48E1	1.68E3	2.84E2	4.54E1	7.07E1	1.15E2	4.25E1	-2.69E2
Water use ¹⁾	m3e depr.	7.55E1	3.63E-1	1.81E0	7.76E1	1.04E0	8.46E-2	2.63E-1	4.74E0	1.96E0	-2.06E1

GWP = Global Warming Potential; EP = Eutrophication potential; POCP = Photochemical ozone formation; ADP = Abiotic depletion potential. 1) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and lonizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator. 2) Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e.

USE OF NATURAL RESOURCES

Results per functional or declared unit											
Impact category	Unit	A 1	A2	A3	A1-A3	A 4	C1	C2	C3	C4	D
Renew. PER as energy	MJ	1.34E2	2.02E0	8.16E1	2.17E2	3.52E0	2.45E-1	8.90E-1	3.62E0	3.43E-1	-2.57E1
Renew. PER as material	MJ	0.00	0.00	7.14E1	7.14E1	0.00	0.00	0.00	0.00	0.00	0.00
Total use of renew. PER	MJ	1.34E2	2.02E0	1.53E2	2.89E2	3.52E0	2.45E-1	8.90E-1	3.62E0	3.43E-1	-2.57E1
Non-re. PER as energy	MJ	1.55E3	6.70E1	6.48E1	1.68E3	2.84E2	4.54E1	7.07E1	1.15E2	4.25E1	-2.69E2
Non-re. PER as material	MJ	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total use of non-re. PER	MJ	1.55E3	6.70E1	6.48E1	1.68E3	2.84E2	4.54E1	7.07E1	1.15E2	4.25E1	-2.69E2
Secondary materials	kg	3.74E1	0.00	0.00	3.74E1	0.00	0.00	0.00	0.00	0.00	9.32E0
Renew. secondary fuels	MJ	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Non-ren. secondary fuels	MJ	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Use of net fresh water	m3	3.06E0	1.62E-2	2.78E-2	3.10E0	5.80E-2	4.01E-3	1.47E-2	1.14E-1	4.64E-2	-9.39E-1

PER = Primary energy resources





END OF LIFE – WASTE

Results per functional or declared unit											
Impact category	Unit	A1	A2	A3	A1-A3	A4	C1	C2	C3	C4	D
Hazardous waste	kg	2.83E1	1.19E-1	2.11E-1	2.86E1	2.78E-1	4.88E-2	6.87E-2	0.00	3.96E-2	-9.44E0
Non-hazardous waste	kg	3.16E2	7.70E0	8.41E0	3.32E2	2.96E1	5.22E-1	7.60E0	0.00	2.88E2	-9.27E1
Radioactive waste	kg	5.97E-3	4.45E-4	1.78E-4	6.59E-3	1.95E-3	3.18E-4	4.85E-4	0.00	2.81E-4	-3.95E-4

END OF LIFE – OUTPUT FLOWS

Results per functional or declared unit											
Impact category	Unit	A1	A2	A3	A1-A3	A 4	C1	C2	C3	C4	D
Components for re- use	kg	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Materials for recycling	kg	0.00	0.00	2,45E0	2,45E0	0.00	0.00	0.00	7,12E2	0.00	0.00
Materials for energy rec	kg	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Exported energy	MJ	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

ENVIRONMENTAL IMPACTS - EN 15804+A1, CML / ISO 21930

Results per functional or declared unit											
Impact category	Unit	A 1	A2	A3	A1-A3	A 4	C1	C2	C3	C4	D
Global Warming Pot.	kg CO2e	2.10E2	4.32E0	4.22E0	2.18E2	1.83E1	3.27E0	4.50E0	4.69E0	1.49E0	-2.76E1
Ozone depletion Pot.	kg CFC11e	9.11E-6	7.42E-7	3.86E-7	1.02E-5	3.42E-6	5.63E-7	8.49E-7	1.29E-6	4.96E-7	-1.11E-6
Acidification	kg SO2e	5.59E-1	1.36E-2	1.94E-2	5.92E-1	5.62E-2	4.87E-3	9.25E-3	2.36E-2	6.01E-3	-1.16E-1
Eutrophication	kg PO4 3e	2.76E-1	3.85E-3	8.73E-3	2.89E-1	9.50E-3	8.57E-4	1.87E-3	6.67E-3	1.16E-3	-7.62E-2
POCP ("smog")	kg C2H4e	4.92E-2	6.74E-4	1.48E-3	5.13E-2	2.80E-3	5.01E-4	5.86E-4	1.47E-3	4.41E-4	-1.71E-2
ADP-elements	kg Sbe	2.19E-3	6.48E-5	5.56E-5	2.31E-3	3.07E-4	5.03E-6	7.75E-5	1.04E-4	1.39E-5	-1.02E-3
ADP-fossil	MJ	1.55E3	6.70E1	6.48E1	1.68E3	2.84E2	4.54E1	7.07E1	1.15E2	4.25E1	-2.69E2





General information

Programme information

Programme:	The International EPD® System						
Address:	EPD International AB Box 210 60 SE-100 31 Stockholm Sweden						
Website:	www.environdec.com						
E-mail:	info@environdec.com						

CEN standard EN 15804 serves as the Core Product Category Rules (PCR)

Product category rules (PCR): PCR 2019:14 Construction products (version 1.1); Complementary PCR (c-PCR):C-PCR-003 (TO PCR 2019:14) - Concrete and concrete elements, version: 2019-12-20;

PCR review was conducted by: The International EPD® System

Independent third-party verification of the declaration and data, according to ISO 14025:2006:

 \square EPD process certification \boxtimes EPD verification

Third party verifier: Vladimir Kočí, LCA Studio

Approved by: The International EPD[®] System

Procedure for follow-up of data during EPD validity involves third party verifier:

⊠ Yes □ No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but from different programmes may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804. For further information about comparability, see EN 15804 and ISO 14025.





References

- General Programme Instructions of the International EPD® System. Version 4.0;
- PCR 2019:14 Construction products (version 1.1)
- EN 15804:2012+A2:2019 Sustainability of construction works. Environmental product declarations. Core rules for the product category of construction products.
- ISO 14020:2001 Environmental labels and declarations General principles.
- ISO 14040:2006 Environmental management. Life cycle assessment. Principles and frameworks.
- ISO 14044:2006 Environmental management. Life Cycle Assessment. Requirements and guidelines.
- ISO 14025:2010 Environmental labels and declarations. Type III environmental declarations. Principles and procedures.

Tools and database

- One Click LCA tool;
- Ecoinvent 3.6 database

Contact information

EPD owner:

Perdanga, UAB www.perdanga.lt



LCA author:

Vesta Consulting, UAB www.vestaconsulting.lt



Programme operator:

The International EPD® System https://www.environdec.com



