

Environmental product declaration for:



Keradecor Super Paint

Organic mineral paint, super-washable,
with a velvety finishing

Programme: The International EPD® System

Programme operator: EPD International AB

EPD registration number: S-P-05631

Publication date: 2022-03-08

Revision date: 2022-05-31

Valid until: 2027-02-28

EPD Validity: 5 years

Geographical scope: Global

CPC Code: 3511 - Paints and varnishes and related products

→ In accordance with ISO 14025 and
EN 15804:2012+A2:2019

→ Independently verified

→ Cradle to Gate scope

→ Product- specific



kerakoll

CONTENTS

1. About this EPD
2. About Kerakoll
3. Manufacturing
4. Products
5. LCA Information
6. Environmental Indicators
7. Environmental Performance
8. Additional Environmental Information
9. Differences versus previous version of the EPD
10. References

1. ABOUT THIS EPD

What is an EPD?

Environmental Product Declaration (EPD) is label that provide a transparent, multi-faceted overview of the environmental performance of a product during its life cycle.

Our intention in providing this EPD is to present the potential environmental impacts for our products.

They are presented in single EPDs such that they can be combined to calculate the impacts of a more complex building system. Target audiences of the study are customers and other parties interested in the environmental impacts of our products. According to EN 15804, EPD of construction products may not be comparable if they do not comply with this standard. EPDs within the same product category from different programs may not be comparable. For further information about comparability, see EN 15804 and ISO 14025.

Declaration owner and LCA Author

KERAKOLL Spa
www.kerakoll.com
info@kerakoll.com
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy

kerakoll

EPD programme and programme operator

The International EPD® System
EPD International AB
Box 210 60
SE-100 31 Stockholm
Sweden
www.environdec.com
info@environdec.com

 **EPD®**

CEN standard EN 15804:2019 served as the core PCR

PCR	EN 15804:2012+A2:2019 as the core PCR, International EPD System PCR 2019:14 "Construction products", v1.11, 2021-02-05
PCR committee	IVL Swedish Environmental Research Institute Secretariat of the International EPD® System
PCR review was conducted by	The Technical Committee of the International EPD® System. See www.environdec.com/TC for a list of members. Review chair: Claudia A. Peña, University of Concepción, Chile. The review panel may be contacted via the Secretariat www.environdec.com/contact .
Independent verification of the declaration and data according to ISO 14025:2006	<input checked="" type="checkbox"/> EPD process certification (Internal) <input type="checkbox"/> EPD verification (External)

Third party verifier

SGS Italia S.p.A.
www.sgsgroup.it
Via Caldera, 21 - 20153 Milano, Lombardia (Italy)

SGS

Accredited by

Accredia - accreditation number: 006H

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

kerakoll

2. ABOUT KERAKOLL

Kerakoll - The GreenBuilding Company

From the outset, the pillar of the Kerakoll vision has always been to make the difference through sustainable innovation. This belief led to the launch of Biocalce and Healthy Building in April 2005, i.e. the new take on sustainable building in which the focus is to safeguard health and improve the quality of life.

Kerakoll became The GreenBuilding Company, the leading manufacturer of green solutions for designing, building and living in harmony with the environment and in healthy spaces: the company earned certification for the GreenBuilding Rating from the Société Générale de Surveillance (SGS) and got the EPD Process Certification, meaning that our internal processes to produce EPDs have been quality assured by an external certification body.

Mission & Vision

To represent GreenBuilding, the new low environmental impact approach to building that safeguards the health and wellbeing of people. We think, develop and produce innovative solutions that focus on the environment and on improving both health and quality of life by using building materials that avoid the most common illnesses caused by indoor pollution. Our vision is to interpret GreenBuilding as a new way of building that is kind on the environment, promoting higher quality homes around the world and helping people to live better.

Products, services and specific know-how formed the basis of Kerakoll's rise to become the GreenBuilding Company, the only company to provide a global GreenBuilding solution that aims at designing, building, and living in harmony with the environment and in healthy spaces.

Values

The Kerakoll business culture to create value over time.

Kerakoll is determined to improve its performance in all ways, firm in the belief that to create value over time you have to first create a firm business culture.

Business culture in Kerakoll means being committed to recognizing and reclaiming the value of key experiences and practices of the past, and at the same time being constantly willing to go out on a limb.

Research and innovation only make sense in such a context, where progress goes hand-in-hand with restoration, preservation and reclaiming the heritage of the company's past.

The Kerakoll mission is to meet the needs of its consumers with a constant supply of new and original ideas, remaining ever faithful to a business culture always ready to consider the ideas of all its members.

When it comes to knowledge assets, people are a key resource for Kerakoll along with the values, expectations, hopes, ideas and originality they bring with them.

This belief is the cornerstone of the Kerakoll business ethos, and the five pillars of this approach represent our *modus operandi* in both life and work.

Integrated policy for total quality, wellbeing and protection of the environment

We pride ourselves on our quality, we are guided by our commitment to society and the health of people, and tireless in our promotion of environmental sustainability.

Focus on the environmental sustainability of a home as it relates to the health of its inhabitants: this is the core philosophy that underlies Kerakoll GreenBuilding. The pillars of healthy housing are indoor air quality, advanced environmental and energy standards, and healthy spaces that exist in harmony with nature. Kerakoll's personal approach aims to integrate the many aspects of GreenBuilding into everyday life, in keeping with the growing environmental sensibility of every individual.

We believe that our mission is to make technology more sustainable and to develop an associated model of development: the true aim of any business should be to develop projects of low environment impact but of huge technological innovation.

Kerakoll's commitment in this direction can be seen in everyday things, in business, and in our awareness of consumer needs in order to satisfy current requirements without jeopardizing the wellbeing of future generations. This is not just an economic mission, but also one of corporate social responsibility which guides and unites everyone here at Kerakoll. That's why at Kerakoll we see business and social responsibility as going hand in hand, which means we make it our business to improve the quality of life of people and the environment they live in.

Taking "Made in Italy" excellence around the world


In its 40 years in the industry, Kerakoll has been so successful that it has gone from being top of the domestic market to a top Italian-based business in Europe, before also becoming a leading European group (and Italian at heart) bound for the international arena. International expansion and an ever more global approach have certainly not eroded the longstanding Kerakoll identity. The company has remained faithful to the values that saw it rise to 1st place in the production of GreenBuilding solutions around the world with more than 1,700 items.

Innovation, respect for the environment, concern for health and living comfort, and a pure wholesome approach are the defining tenets of Kerakoll.

3. MANUFACTURING

The manufacturing process starts from raw materials purchased from suppliers and stored in the plant. Bulk raw materials are stored in specific silos and added mostly automatically in the production mixer, according to the formula of the products. Other raw materials, supplied in bags or big bags, are stored in their warehouse and added automatically or manually in the mixer.

The production is a discontinuous process, in which all the components are mechanically mixed in batches. The semi-finished products are then packaged in bags, put on wooden pallets, covered by stretched hoods and stored in the Finished Products' warehouse. The quality of final products is controlled before the sale.



4. PRODUCTS

Description and use of the product

The product is manufactured by Kerakoll S.p.A. in the production plant located in Zimella (VR - Italy). Organic, mineral, super-washable and breathable paint intended for internal use. Keradecor Super Paint is based on water-based styrene-acrylic resins. It is super-washable and resistant to mould. The paint contains antibiodeteriorating additives, offers excellent coverage, bright white and has a velvety finish. The product is supplied in 4 and 14 L plastic buckets format.



Physical characteristics

The product is in a liquid form, the first and second coats should be diluted with water by up to 30 - 40% of the total volume depending on requirements and the tools used.

Content declaration

The main components of the Keradecor Super Paint are the following:


Component	Weight (%)	Comment (i.e. recycled materials)	EC	CAS Nr.	Classification
Water	30-50	-	231-791-2	7732-18-5	-
Fillers	25-55	-	207-439-9	471-34-1	-
	10-20	-	215-279-6	1317-65-3	-
Pigments	0-1	-	236-675-5	13463-67-7	-
Resins	<0,5	-	500-016-2	9004-98-2	H315, H400
Additives	<0,01	-	203-603-9	108-65-6	H226, H336
	<0,02	-	200-143-0	52-51-7	H335, H315, H318, H400, H302, H312, H410
	<0,05	-	220-120-9	2634-33-5	H302, H315, H317, H318, H400
	<0,03	-	236-671-3	13463-41-7	H301, H318, H330, H360D, H372, H400, H410
	<0,0015	-	611-341-5	55965-84-9	H301, H310, H314, H317, H318, H330, H400, H410
	<0,0015	-	247-761-7	26530-20-1	H330, H311, H301, H314, H318, H317, H400, H410
	<0,0015	-	264-843-8	64359-81-5	H330, H302, H314, H318, H317, H400, H410

Product is free from substances of very high concern (SVHC) on the REACH Candidate List published by the European Chemicals Agency in a concentration more than 0,1% (by unit weight). Related to specific components, the table above shows only hazardous ones within the meaning of the CLP regulation and their related classification as stated into product Safety Data Sheet. The primary packaging is a plastic bucket. The most representative one, in terms of market supply, is the 14 L format. The main characteristics are shown in the table below.

Primary packaging	Weight (kg)	Weight (%), finished product
Plastic bucket	0,7	3,3 %

5. LCA INFORMATION

Declared Unit and Reference Service Life



The Declared Unit (DU) is 1 kg of product (paint).

This document describes the environmental impact of 1 kg of paint (packaging included). According to the system boundary of this EPD, a RSL has not been provided.

Scope

CEN developed the EN 15804:2012+A2:2019, a core set of rules for the development of EPD applicable to construction products. This standard is developed with a modular structure, described below. This EPD is of the "Cradle to Gate" type, including EN 15804 modules from A1 to A3. Modules not accounted in the LCA since they are not assessed are marked as "ND", Not Declared.

	Upstream - Core			Downstream												
	Product stage			Construction process stage		Use stage							End of life stage			
	Raw material supply	Transports (raw materials - pack)	Manufacturing	Transport to customer	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport to waste	Waste processing	Disposal
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4
Modules declared	X	X	X	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Geography	IT	IT	IT	-	-	-	-	-	-	-	-	-	-	-	-	-
Specific data used	>90%			-	-	-	-	-	-	-	-	-	-	-	-	-
Variation - products	Not relevant			-	-	-	-	-	-	-	-	-	-	-	-	-
Variation - sites	Not relevant			-	-	-	-	-	-	-	-	-	-	-	-	-

System boundaries and processes included in the LCA (X included, ND: Not Declared)

The “Cradle to Gate” type adopted is justified since:

- the product or material is physically integrated with other products during installation so they cannot be physically separated from them at end of life, and
- the product or material is no longer identifiable at end of life as a result of a physical or chemical transformation process, and
- the product or material does not contain biogenic carbon

The EPD is of a product-specific type. However, different colours are available for the single product analysed. Therefore, a sensitivity analysis has been performed. Two extremes colours have been identified, according to their amount of pigments: lightest and darkest one. A sensitivity analysis has been performed between these two colours and the results show that a variation of GWP-GHG indicator for A1-A3 is not larger than $\pm 2\%$ respect to the mean value. Therefore, a representative formula for all the colours available has been adopted. The EPD is therefore representative for all the colours available.

A worst-case approach has been followed when required, like for transports.

Product (A1-A3)

- A1-A2: extraction, supply and transport of raw materials and packaging to Kerakoll and manufacturing process energy consumption.

- A3: manufacturing process of product and its packaging and waste management from the same process.

It covers dosage and mixing of selected and measured raw materials and additives to ensure that the product meets desired properties and packaging material consumption.

Packaging product materials consist of wooden pallet, cardboard and LDPE used as wrapping material and they include both distribution and consumer packaging, as follows.

Material	Distribution packaging	Consumer packaging
Wooden pallet	x	
Plastic and LDPE film (e.g. for wrapping material)	x	
Plastic bucket		x

Data quality

For the background data the Ecoinvent v.3.7 database is used. Raw materials and packaging, energy and water consumption and waste data are collected from Kerakoll. The most relevant considered data are European or specific from supplier. Generic and producer specific data are not more than 10 and 5 years old respectively (according to EN 15804 6.3.8.2. “Data quality requirements”).

Period under review

All primary data collected from Kerakoll are representative for the year 2020, except for raw materials which are referred to the period january-december 2021.

Allocations

There are no co-products in the production of paints manufactured by Kerakoll. Hence, there is no need for co-product allocation. The Company sources raw materials from different locations across Europe and other parts of the world and by different means of transport. For this reason, transport is allocated according to raw material quantities.

Kerakoll manufactures various products with specifications for different applications in its different manufacturing plants. Raw materials, transport, energy consumption during manufacturing, packaging and waste data are allocated using data from Kerakoll involved plants.

Cut-off rules

The consumption of auxiliary materials and waste related to extraordinary activities (A3), having a periodicity exceeding 3 years, are excluded. Quantified contribution from those process: less than 0,5% by mass of products.

6. ENVIRONMENTAL INDICATORS

An introduction to each environmental indicator is provided below. All indicators represent the potential to cause environmental impacts; they do not predict if specific environmental thresholds, safety margins or risks will be exceeded. The actual impacts on the environment typically depend upon local, regional and/or global conditions.

Acidification Potential (AP)

- Acid Rain

A measure of emissions that cause acidifying effects to the environment. Acidification potential is a measure of a molecule's capacity to increase the hydrogen ion (H⁺) concentration in the presence of water, thus decreasing the pH value. Potential effects include forest decline and the deterioration of building materials.



Eutrophication Potential (EP)

- Algal Blooms

A measure of nutrient enrichment that may cause an undesirable shift in species composition and elevated biomass production in both terrestrial and aquatic ecosystems. It includes potential impacts of excessively high levels of macronutrients, the most important of which are nitrogen and phosphorus.



Water Deprivation Potential (WDP) - Water Use

It represents the relative available water remaining per area in a watershed, after the demand of humans and aquatic ecosystems has been met. It assesses the potential of water deprivation, to either humans or ecosystems, building on the assumption that the less water remaining available per area, the more likely another user will be deprived.

Abiotic Depletion Potential (ADP)

- Resource Consumption

The consumption of non-renewable resources leads to a decrease in the future availability of the functions supplied by these resources. Depletion of mineral resource elements (ADPE) and non-renewable fossil energy resources (ADPF) are reported separately.



Ozone Depletion Potential (ODP) - Ozone Hole

A measure of greenhouse gas emissions, such as carbon dioxide and methane. These emissions increase absorption of radiation emitted by the earth, intensifying the natural greenhouse effect.



Photochemical Ozone Creation Potential (POCP) - Smog

A measure of emissions of precursors that contribute to ground level smog formation (mainly ozone O₃), produced by the reaction of volatile organic compounds (VOCs) and carbon monoxide in the presence of nitrogen oxides under the influence of UV light. Ground level ozone may be harmful to human and ecosystem health and may also damage crops.



Global Warming Potential (GWP) - Climate Change

A measure of greenhouse gas emissions, such as carbon dioxide and methane. These emissions increase absorption of radiation emitted by the earth, intensifying the natural greenhouse effect.

7. ENVIRONMENTAL PERFORMANCE

All results are referred to the Declared Unit that is 1 kg of paint (packaging included).

POTENTIAL ENVIRONMENTAL IMPACTS	Unit	TOTAL A1-A3	A1	A2	A3
Climate change (GWP-total)	kg CO ₂ eq	1,22E+00	1,14E+00	7,62E-02	1,13E-02
Climate change - Fossil (GWP-fossil)	kg CO ₂ eq	1,32E+00	1,11E+00	7,55E-02	1,41E-01
Climate change - Biogenic (GWP-biogenic)	kg CO ₂ eq	-1,07E-01	2,25E-02	6,17E-04	-1,30E-01
Climate change - Land use and LU change (GWP-luluc)	kg CO ₂ eq	8,19E-03	8,00E-03	2,87E-05	1,63E-04
Ozone depletion (ODP)	kg CFC-11 eq	4,57E-07	4,22E-07	1,63E-08	1,83E-08
Acidification (AP)	mol H ⁺ eq	1,87E-02	1,79E-02	3,16E-04	4,56E-04
Eutrophication, freshwater (EP-freshwater)	kg P eq	4,60E-04	4,18E-04	6,61E-06	3,48E-05
Eutrophication, freshwater (EP-freshwater)	kg PO ₄ eq	1,41E-03	1,28E-03	2,03E-05	1,07E-04
Eutrophication, marine (EP-marine)	kg N eq	1,56E-03	1,35E-03	9,45E-05	1,07E-04
Eutrophication, terrestrial (EP-terrestrial)	mol N eq	1,40E-02	1,18E-02	1,03E-03	1,12E-03
Photochemical ozone formation (POCP)	kg NMVOC eq	4,91E-03	4,21E-03	3,12E-04	3,94E-04
Resource use, minerals and metals (ADP-minerals&metals) ¹	kg Sb eq	1,49E-05	1,41E-05	2,86E-07	4,85E-07
Resource use, fossils (ADP-fossil) ¹	MJ	2,04E+01	1,76E+01	1,13E+00	1,75E+00
Water use (WDP) ¹	m ³ depriv.	1,34E+00	1,30E+00	5,60E-03	3,41E-02

ADDITIONAL ENVIRONMENTAL IMPACTS	Unit	TOTAL A1-A3	A1	A2	A3
Particulate matter (PM)	disease inc.	8,57E-08	7,61E-08	5,00E-09	4,66E-09
Ionising radiation (IRP) ²	kBq U-235 eq	1,36E-01	1,12E-01	6,16E-03	1,76E-02
Ecotoxicity, freshwater (ETP-fw) ¹	CTUe	4,28E+01	3,96E+01	8,96E-01	2,37E+00
Human toxicity, cancer (HTP-c) ¹	CTUh	2,97E-09	2,70E-09	3,95E-11	2,36E-10
Human toxicity, non-cancer (HTP-nc) ¹	CTUh	3,25E-08	2,95E-08	8,75E-10	2,16E-09
Land use / Soil quality (SQP) ¹	Pt	1,57E+01	6,04E+00	7,71E-01	8,94E+00

¹ Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator

² Disclaimer: This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear full cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

USE OF RESOURCES	Unit	TOTAL A1-A3	A1	A2	A3
Use of non-renewable primary energy excluding resources used as raw materials - PENRE	MJ	2,19E+01	1,89E+01	1,20E+00	1,86E+00
Use of non-renewable primary energy resources used as raw materials - PENRM	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Total use of non-renewable primary energy resources - PENRT	MJ	2,19E+01	1,89E+01	1,20E+00	1,86E+00
Use of renewable primary energy excluding resources used as raw materials - PERE	MJ	3,28E+00	1,57E+00	3,02E-02	1,68E+00
Use of renewable primary energy resources used as raw materials - PERM	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Total use of renewable primary energy resources - PERT	MJ	3,28E+00	1,57E+00	3,02E-02	1,68E+00
Use of secondary material - SM	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of renewable secondary fuels - RSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of non-renewable secondary fuels - NRSF	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of net fresh water - FW	m3	3,44E-02	3,30E-02	1,94E-04	1,24E-03

WASTE PRODUCTION AND OUTPUT FLOWS	Unit	TOTAL A1-A3	A1	A2	A3
Hazardous waste disposed - HWD	kg	3,66E-02	0,00E+00	0,00E+00	3,66E-02
Non-hazardous waste disposed - NHWD	kg	1,44E-02	0,00E+00	0,00E+00	1,44E-02
Radioactive waste disposed - RWD	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00

GWP-GHG (according to IPCC 2013)	Unit	TOTAL A1-A3	A1	A2	A3
Climate change (GWP-total IPCC 2013) ³	kg CO ₂ eq	1,31E+00	1,09E+00	7,49E-02	1,40E-01

BIOGENIC CARBON CONTENT	Unit	A1 - product	A3 - packaging
Biogenic Carbon content ⁴	kg C	0,00E+00	3,55E-02

³ The indicator includes all greenhouse gases included in GWP-total but excludes biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. This indicator is thus almost equal to the GWP indicator originally defined in EN 15804:2012+A1:2013.

⁴ 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

8. ADDITIONAL ENVIRONMENTAL INFORMATION

Quality and Environmental management systems

Kerakoll is ISO 9001 certified since 2000 and ISO 14001 since 2012.

VOC emissions

Keradecor Super Paint is marked as "A" according to French VOC regulation. The regulation (Décret n° 2011-321) provides information on the level of emission of volatile substances in the indoor air on a class scale from A+ (very low emissions) to C (high emissions).

9. DIFFERENCES VERSUS PREVIOUS VERSION OF THE EPD

Some data updating to ensure the relevance and validity of the document for the product involved.

10. REFERENCES

Ecoinvent - Ecoinvent Centre, www.ecoinvent.org

EN 15804:2012+A2:2019 - Sustainability of construction works - Environmental Product Declarations - Core rules for the product category of construction products

EN ISO 16000-9:2008-04 - Indoor air – Part 9: Determination of the emission of volatile organic compounds from building products and furnishings – Emission test chamber method

Arrêté étiquetage 2011 - Arrêté du 19 avril 2011 relatif à l'étiquetage des produits de construction ou de revêtement de mur ou de sol et des peintures et vernis sur leurs émissions de polluants volatils

EPD Study Report - Interior white paints, 2022-02-15

GPI - General Programme Instructions, The International EPD® System, Version 3.1

ISO 9001:2015 - Quality management systems - Requirements

ISO 14001:2015 - Environmental management systems - Requirements with guidance for use

ISO 14021:2016 - Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling)

ISO 14025:2009 - Environmental labels and declarations - Type III environmental declarations - Principles and procedures

ISO 14040/44:2006 - Environmental management - Life cycle assessment - Principles and framework (ISO 14040:2006) and Requirements and guidelines (ISO 14044:2006)

ISO 16000-3:2013-01 - Indoor air –Part 3: Determination of formaldehyde and other carbonyl compounds by sampling using a pump

ISO 16000-6:2012-11 - Indoor air –Part 6: Determination of volatile organic compounds indoors and in test chambers by sampling on TENAX TA®, thermal desorption and gas chromatography using MS or FID

PCR for Construction Products, The International EPD System, 2019:14 Version 1.11, 2024-12-20

SimaPro - SimaPro LCA Software, Pré Consultants, the Netherlands, www.pre-sustainability.com

The International EPD® System - The International EPD® System is a programme for type III environmental declarations, maintaining a system to verify and register EPD®s as well as keeping a library of EPD®s and PCRs in accordance with ISO 14025 www.environdec.com

All rights reserved. © Kerakoll. All rights to the content of this publication are reserved in accordance with applicable law. The duplication, publication and distribution, in full or in part, of all material contained herein are expressly forbidden without written authorization.